



1. ALL RESISTORS IN OHMS. ALL RESISTORS 0.5W UNLESS MARKED OTHERWISE.
2. ALL CAPACITORS IN MICROFARADS UNLESS OTHER PREFIX MARKED, THEN REPLACE PREFIX (MICRO) IN UNIT (MICROFARAD) WITH MARKED PREFIX. ALL CAPACITORS 25V (MINIMUM VOLTAGE RATING) UNLESS MARKED OTHERWISE.
3. ALL VOLTAGES IN VOLTS.
4. TRANSISTORS Q1, Q2, Q3: 2N5086.
5. TRANSISTORS Q4, Q5: MPSA56.
6. TRANSISTORS Q6, Q7: MPSA06.
7. TRANSISTOR Q8: 2N4918.
8. TRANSISTOR Q9: 2N4921.
9. DIODES D1, D2, D3, D4, D5, D6: 1N4002.
10. LAST REFERENCED DESIGNATION ON SCHEMATIC: R19, C8, Q9, D6, P8.

**RIC** Rickenbacker International Corp.  
 3895 S. Main Street  
 Santa Ana, Ca. 92707  
 Tel: 714-545-5574 Fax: 714-754-0135

**SCHEMATIC, POWER AMP RG7**

SCALE	NA	CHECKED BY	DRAWN BY
DATE	3/10/89	J. HALL	K. MASCARENHAS
SIZE	B	DRAWING NO 19324	